

Walker Bag Measurements (Updated 2/25/2026)

Based Upon Tagliarini You Tube Video

1. Cut two pieces of fabric 16" by width of fabric. Use the width of the smaller of the two fabrics, approximately 43". Cut one from heavy weight fabric (such as upholstery or decorator weight) and one from regular cotton. If you use 2 pieces of regular cotton, you need to add fusible medium weight stabilizer or light weight batting to make it sturdy.
2. Sew right sides together using a 3/8" or 1/2" seam. Leave about a 3" to 4" opening for turning. Clip corners and turn.
3. After turning and pressing, top stitch 1/4" on the short ends. This will be the stitching that shows on the top of the pocket.
4. Cut 2 pieces of Velcro 3.5" or 4" long.
5. The Velcro is attached to the side of the fabric that will show on the pocket when the ends of the fabric sandwich are turned up. Pick the one you like best as most of it will be seen on the outside of the pocket. Stitch the Velcro 5" from the center of the length and 1.5" inches down from the outside edge. Refer to diagram below for placement. Sew all 4 pieces of Velcro being sure that the hook and loop are on opposite sides of the center.
6. After Velcro is attached make the pockets. Fold the bottom up 8 1/2" to form the pocket. Attach pocket to the back with clips or pins along the side. Do this on both ends so you will have formed two pockets. Sew the side seams end to end on both sides with 1/4" seam. Be sure to get the opening from turning sewn closed. Re-enforce top edge of pocket with back stitching.
7. Divide pockets in half by stitching up the middle on each pocket. Back stitch at the top of the pocket to re-enforce it.